



(800) 247-5548


www.sonictechnology.com

SuperEar® PERSONAL SOUND AMPLIFIER

LCS110	SIZE	UNITS / WEIGHT	HS TARIFF CODE
CASE	15" x 10" x 8.8"	6 / 8.0 lbs	8525. 60. 2000
GIFTBOX	9.5" x 6.5" x 1.5"	1 / 1 lb	



Transmitter and Receiver units



PRODUCT HIGHLIGHTS

- 3 Year Warranty
- Up to 150 ft. Wireless Audio
- 3 FM channels
- Broadcast to multiple receivers

Lightweight, premium quality stereo Earbuds

One transmitter can broadcast to multiple receivers (sold separately), perfect for large groups, meetings and tour guides.

**may also be used with headphones, sold separately*

LCS110 Set comes with:



LCT100 TRANSMITTER UNIT

Microphone	50dB gain, multielement, integrated
Body frame material	High Impact ABS
Max Output	107 dB
Humidity Operating Range:	At 20°C, 95% RH
Dimensions	3.05" x 2" x 0.75"
Frequency Switch	3-position, user selectable
Plug-in connector	Stereo jack, 3.5mm diameter
Power Source	2-AA Ni-MH batteries (rechargeable)
USB Charger	110/240VAC, USB to Mini-B jack
Operation time	Approx. 11 hours between recharge
Belt/Pocket/Clip	included
3.5 mm Audio-in connector	for connecting external audio sources such as TV, Computer, Ipod®, etc.

LCR100 RECEIVER UNIT

Automatic Shut Off	No
Body frame material	High Impact ABS
Max Output	107 dB
Reception distance	Up to 150 ft
Frequency Switch	72.2, 72.8 and 75.8 MHz, selectable
Frequency Range	100Hz -14KHz
Plug-in connector	Stereo jack, 3.5mm diameter
Power Source	2-AA Ni-MH batteries (rechargeable)
Weight	3 oz.
Belt/Pocket/Clip	included

EARBUDS (LC-EB)

Diaphragm	Mylar, diameter 10mm.
Impedance	32 ohms +/- 15% at 1KHz
Nominal Power	5mW
Max Power	10mW
Sensitivity	105 dB S.P.L +/- 3dB at 1KHz
Balance per channel	+/- 3dB at 1KHz
Frequency Response	20Hz-20 KHz
Plug-in connector	Stereo Plug, 3.5mm diameter
Cord Length	1150mm +/- 50mm
THD	Less than 5% at 1KHz 0.126V